					Frequency Band		Description	
COMMUNICATIONS RESOURCE AVAILABILITY WORKSHEET							St Clair County	
Channel Configuration	Channel Name/Trunked Radio System Talkgroup	Eligible Users	RX Freq N or W	RX Tone/NAC	TX Freq N or W	Tx Tone/NAC	Mode A, D or M	Remarks
Repeater	WA9QME	ALL	146.85	107.2	146.250 W		Α	Also serves as SKYWARN BU
Packet	ARES Packet	ARES	145.07	CSQ	145.07		Digi	ARES Statewide Packet
HV Call	ARES Statewide	ARES	146.55	CSQ	146.55		Α	Statewide Call
HU Call	ARES Statewide	ARES	446	CSQ	446		Α	Statewide Call
HM Call	ARES Statewide	ARES	52.55	CSQ	52.55		Α	Statewide Call
HV Tac 4	District D	ARES	146.4	CSQ	146.4		Α	District D Call
6 M Scene	District D	ARES	52.45	CSQ	52.45		Α	Working Scene
SCCARES Tac 1	Local ARES	ARES	146.49	CSQ	146.49		Α	Local Tac before MO EOP
MESN	ARES	ARES	7.263	NA	7.263		Α	MESN Daytime
MESN	ARES	ARES	3.963	NA	3.963		Α	MESN Nightime
Dist. D HF	ARES	ARES	3.973	NA	3.973		Α	Net on Sunday 1600 local

The convention calls for frequency lists to show four digits after the decimal place, followed by either an "N" or a "W", depending on whether the frequency is narrow or wide band. Mode refers to either "A" or "D" indicating analog or digital (e.g. Project 25) or "M" indicating mixed mode. All channels are shown as if programmed in a control station, mobile or portable radio. Repeater and base stations must be programmed with the Rx and Tx reversed.

ICS 217A Excel 3/2007