COMMUNICATIONS RESOURCE AVAILABILITY WORKSHEET					Frequency Band		Description	
Channel Configuration	Channel Name/Trunked Radio System Talkgroup	Eligible Users	RX Freq N or W	RX Tone/NAC	TX Freq N or W	Tx Tone/NAC	Mode A, D or M	Remarks
REPEATER	TC ARES TAC 2	AMATEUR	147.1500 W	NA	147.7500 W	NA		KC0M/R TANEY ARES TAC 2
REPEATER	TC ARES TAC1	AMATEUR	147.1950 W	NA	147.7950 W	NA	Α	KC0M/R TANEY ARES TAC 1
SIMPLEX	TC ARES TAC 3	AMATEUR	146.5500 W	NA	146.5500 W	NA	Α	SIMPLEX TANEY ARES TAC3
	_							
	+							
	+							

The convention calls for frequency lists to show four digits after the decimal place, followed by either an "N" or a "W", depending on whether the frequency is narrow or wide band. Mode refers to either "A" or "D" indicating analog or digital (e.g. Project 25) or "M" indicating mixed mode. All channels are shown as if programmed in a control station, mobile or portable radio. Repeater and base stations must be programmed with the Rx and Tx reversed.

ICS 217A Excel 3/2007