COMMUNICATIONS RESOURCE AVAILABILITY WORKSHEET

Frequency Band: **Amateur**

Description: **St. Louis Metro ARES**

	Channel Configuration	Channel Name/Trunked Radio System Talkgroup	Eligible Users	RX Freq	N or W	RX Tone/NAC	TX Freq	N or W	Tx Tone/NAC	Mode A, D or M	Remarks
	Repeater	WØSRC	Amateur	146.250	W	141.3	146.850	W	141.3	A	WØSRC Repeater
	Simplex	HVTac 10	Amateur	147.510	W	N/A	147.510	W	N/A	A	HVTac 10
	Simplex	HVTac 11	Amateur	146.415	W	N/A	146.415	W	N/A	A	HVTac 11
	Simplex	HVTac 12	Amateur	147.435	W	N/A	147.435	W	N/A	A	HVTac 12
	Simplex	HVTac 13	Amateur	146.535	W	N/A	146.535	W	N/A	A	HVTac 13
	Simplex	HVTac 14	Amateur	147.585	W	N/A	147.585	W	N/A	A	HVTac 14
	Simplex	Packet	Amateur	145.070	W	N/A	145.070	W	N/A	D	Packet
	Simplex	APRS	Amateur	144.390	W	N/A	144.390	W	N/A	D	APRS

The convention calls for frequency lists to show four digits after the decimal place, followed by either an “N” or a “W”, depending on whether the frequency is narrow or wide band. Mode refers to either “A” or “D” indicating analog or digital (e.g. Project 25) or "M" indicating mixed mode. All channels are showr as if programmed in a control station, mobile or portable radio. Repeater and base stations must be programmed with the Rx and Tx reversed.